

ZTS101A Controller

Pan, Tilt, Zoom, Focus and DVR control

iNNEKT

Innovative Technology

Features

- Recalls up to 255 cameras from one keyboard
- Multi-protocol supported in each channel (PELCO-D, P)
- Preset position control
- Various manual control speed (1 ~ 64 steps)
- Maximum speed is changed according to zoom ratio
- Recalls programmed guard tours from each dome camera
- Built in LCD Display with blue screen
- Programmable user preference. (tour, preset, pattern, auto-scan, etc.)
- User password and system hold function
- Supports DVR Protocol (Need to be modified)
- Slave Communication to RS232
- Maximum speed is changed according to zoom ratio
- Recalls programmed guard tours from each dome camera
- Built in LCD Display with blue screen



Controller

Specification

Communication	Master : RS485 (2400bps, 4800bps, 9600bps) Slave : RS232 (2400bps, 4800bps, 9600bps)
Joystic	3 Axis Zoom IN / OUT available
Power Consumption	DC 12V, 110mA
Display Type	16 x 2 Character LCD, With Blue Backlight
Key Type	PC Keyboard Button
Keyboard Connector Type	RJ45 8 Pin Modular Cable
Junction Box Connector	Master : Terminal Block Slave : 9 Pin D-SUB Connector, 8 Pin Modular
Humidity	10% ~ 70% non Condensing
Dimension	140(W) x 185(H) x 365(D)mm
Weight	1.2kg