

ZTS510N Mini PTZ Cameras

Powerful Speed with Silence / 10xOptical Mini PTZ

iNNEKT

Innovative Technology

Features

- 0.02° dome system accuracy
- Filter Changeable Type Day & Night
- Max 200° / sec Pan & 150° sec Tilt speed (on preset mode)
- Vandal-proof Poly carbonate clear dome cover(IP66)
- Communication Protocol System : RS-485
- International Standards : CE, FCC
- Reliable & durable mechanism
- OSD for camera control



Specification

10X PTZ Indoor

Image Sensor	1/4" Sony Super HAD CCD
Total Image Pixels	PAL : 795(H) x 596(V) 470K
Lens	10X Optical Zoom f3.8 ~ 38.0mm (F1.8) / 10X Digital Zoom
Resolution	500 TVL
Day & Night	Auto / Day / Night
Minimum Illumination	Normal mode : 0.7Lux F1.8 (50IRE) Night mode : 0.02Lux F1.8 (50ICE) on DSS mode
Luminance S/N Ratio	More than 50dB
Video Output	Composite Video Output 75 Ω terminated
BLC	ON / OFF
Flickerless	ON / OFF (1/120)
Pan Rotation Angle	360° Endless
Pan Speed	Manual : Max 150° / sec Preset : Max 200° / sec
Tilt Rotation Angle	0° ~ 90°
Tilt Speed	Manual : Max 150° / sec Preset : Max 150° / sec
Presets	165 positions with 16 character labels available for each position
Group Tour	Max. 8 Programmable group tours (each one consisting of up to 60 preset steps with different steps)
Auto scan	Programmable Auto Scan
Pattern	8 Programmable Patterns tour
Sector	8 Selectable Sectors
Password Protection	Yes
Privacy Masking Zone	4 Programmable privacy masking zones
Alarm Input	4 alarms OFF/NC/NO (with various programmable states)
Alarm Actions	Activate preset, tour and Patterns
Alarm Output	-
Auto Flip	ON / OFF
OSD Menu	Multiple Languages on screen
Communication	RS-485
Protocol	Pelco D/P , VICON , SAMSUNG
Power Consumption	DC 12V : 750mA, 10W MAX (1.3A With Heater)