

ZTS536N PTZ Cameras Indoor

WDR True Day & Night Powerful SPEED with Silence

iNNEKT

Innovative Technology

Features

- World's Most Silent Camera
- 0.024° dome system accuracy
- Preset Position Compensation Function
- Slip Ring for Long Life Time (more than 20 million rotation)
- Controlling Pan / Tilt Speed while zooming
- Built-in power-line surge protection and lightening protection
- Quick Operation Keys



36X PTZ Indoor

Specification

Image Sensor	1/4" Sony Exview HAD CCD
Resolution	WDR 530 TVL
Optical Zoom	36X (F= 1.6 ~ 4.5 / f=3.4 ~ 122.4mm)
Digital Zoom	12X Digital Zoom
Day & Night (ICR)	Auto / Day / Night
Digital Slow Shutter	ON / OFF
Minimum Illumination	Color : 0.1Lux ; B/W : 0.01Lux
Luminance S/N Ratio	More than 50dB
Video Output	Composite Video Output 75 Ω terminated
BLC	ON / OFF
Flickerless	ON / OFF
Pan Rotation Angle	360° Endless
Pan Speed	Manual : 0.5° ~ 100°, 200° / sec Preset : Max 300° / sec
Tilt Rotation Angle	-2° ~ 90°
Tilt Speed	Manual : 0.5° ~ 45° / sec (64 step) Preset : Max 250° / sec
Presets	165 positions with 16 character labels available for each position with different speed steps
Group Tour	Max. 8 Programmable group tours (each one consisting of up to 60 preset steps with different steps)
Auto pan	Programmable Auto Scan
Pattern	8 Programmable Auto Scan
Sector	8 Selectable Sectors with 16 characters
Password Protection	Yes
Privacy Zone	24
Alarm Input	4 alarms (with various programmable states)
Alarm Actions	Activate preset, Group scanning or Pattern per alarm input
Alarm Output	2 Replay Output
Auto Flip	ON / OFF
OSD Menu	Yes
Communication	RS-485
Protocol	Multiple protocols
Power Consumption	18W Max
Power Supply	AC 18 ~ 32V , 60/50Hz , 850mA