

# KPC131E

## REGULAR CAMERA



### ● OVERVIEW

Equipped with a 1/3" H.R. Color CCD image sensor, this regular camera possesses satisfactory minimum illumination to provide clear and sharp images and has a microphone built-in to consolidate the quality of your surveillance system.

### ● FEATURES

- (1) High quality picture
- (2) Satisfactory minimum illumination of 0.1 Lux/F2.0
- (3) Audio function supported
- (4) Auto Electronic Shutter built-in
- (5) Signal-to-noise ration of 48dB

### ● SPECIFICATIONS\*

Model	KPC131E
Pick up Element	1/3" H.R. Color CCD image sensor
Number of Pixel	512(H) x 492(V) <NTSC> / 512(H) x 582(V) <PAL>
Resolution	500 TV Lines
Minimum illumination	0.1 Lux / F2.0
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.
Lens Mount	C/CS mount changeable
IRIS Mode	D.D./V.D./AES
AGC	Auto
White Balance	ATW
Video Output	1.0 Vp-p composite, 75Ω
Microphone	YES
Power Source(±10%)	DC12V
Current Consumption(±10%)	80mA
Power Consumption(±10%)	--
Dimension (mm)**	108(L) x 62(W) x 50(H)

\* The specifications are subject to change without notice.

\*\* Dimensional Tolerance: ±5mm