

DT-V31 2.8" LCD Display CCTV PTZ Camera Security Tester

Monitor Multimeter Digital Zoom 12V 1A Output

Features:

- -With unique digital zoom function, the video image can be magnified;
- -2.8 inch high resolution LCD screen, 320 x RGB x 240(QVGA) Resolution, 64K colors.
- -LCD screen brightness/ contrast/color saturation/backlight brightness is adjustable.
- -Video Format NTSC, PAL automatically adapt and standard prompt.
- -Video Signal strength measurement, to test if video signal level is attenuated.

Specifications:

| | |
|--------------------------|--|
| Model | DT-V31 |
| Product Name | CCTV Security Tester |
| Video Test | |
| Video System | NTSC/PAL Automatically Recognize |
| Display Screen | 2.8 inch LCD 320 X RGB X 240(QVGA) Resolution, 64K Color |
| Screen Adjustment | Video Display brightness, contrast, color saturation adjustable, LCD backlight brightness is adjustable. |
| Video Output/Input | 1 Channel BNC Video IN, 1 Channel BNC Video Output |
| Video Analysis | |
| Signal Level Measurement | Measure the video signal level, and displays exception information support "fit screen" "1X" "2X" "4X" options |
| 12V Power Output | |
| Power Output | Temporary Power Output 12V 1A DC |
| Audio Test | |
| Audio Test | Input audio signal, and played on the internal speaker |

PTZ control test

Communication Interface RS485/RS422 bus support

PTZ Protocol Built-in pelco-D/P, for Samsung, Panasonic, Lilin, Yaan...Totally over 30 Protocols

Baud Rate 150, 300, 600, 1200, 2400, 4800, 9600, 19200b

Video Signal

Video Signal Generator Support PAL/NTSC formats, a variety of standards video signal test

Data Monitor

Data Monitor RS485/RS422 bus support, capture and display data.

Power Supply

External Power Supply DC 5V(2A)

Battery-powered Built-in 3.7V Li-polymer battery, Capacity 3000mAh charge time 3 - 4 hours

Charge Battery Power Time 14 Hours

Power Saving Features Low Power consumption, automatic power off, Real-time display of battery level.

System Settings

Language Settings English User Selectable, seven languages support, Russian, Italian, French etc.

Auto Power Off Disable/5 to 60minutes

Keyboard Sound On/Off

Working Environment and Specifications

Temperature -20 to 70 Celsius

Humidity 30% to 90%

Dimension 165 x 80 x 27mm(L*W*T)

Package Contents:

- 1 x CCTV Security Tester
- 1 x BNC Cable
- 1 x Power Adapter
- 1 x 3.5mm Power Cable
- 1 x **Test leads**
- 1 x RS485 Data Cable
- 1 x Audio Testing Cable
- 1 x Battery
- 1 x User Manual
- 1 x Hold Bag