

WALL RACK



19"GERMANY
EXPORT RACK

G1 SERIES




A



B



Master Key w/logo



Roller



Hinge w/logo



Mounting Pole



Two Plies Steel

Feature

- ❖ **Designed and Manufactured** to comply with the standard of ANSI/EIA-310D-1992 (Rev.EIA-310C), IEC60297-1, IEC60297-2, BS5954 Part : 2, DIN 41494.
- ❖ **Three sections** design Front Door, Center Part and Back Base Box.
- ❖ **Produced** from Electro-Galvanized Sheet Steel thickness of 1.2 mm. Mounting Pole, made of 2.0 mm.
- ❖ **Mounting Pole** were designed to be L-shape angle in order to increase the strength. Punching of square mounting hole 10 x 10 mm. They can be adjusted in/out freely to meet customer's needs. And provide the U-height screened on the mounting pole.
- ❖ **Front Door** (for model G1-XXXXX) is the steel frame with acrylic 5.0 mm. thickness with film protection and the width of acrylic is 38 cm. (the height is being influenced by the size of the rack) Door edge is bore with gray dust-proof rubber seal (3 fins). Top the front door has embossed trademark. Security locks with 19" Germany Master Key. For model G1-XXXXXP is the steel door with perforated capsule ventilation 50% of door's area.
- ❖ **Center Part** has sliding rail for adjusting the mounting pole throughout the whole depth of this part. The bottom equipped with rollers. The top has a pre-punch fan pattern for 1 to 3 Fans and on the both side has ventilation grills. Security lock with 19" Germany Master Key which is the same set as the front door.
- ❖ **Back Base Box** has the clip 10 x 10 cm. for cable access in the top and bottom. Hanger slot for screw on the back part is the two plies steel with 2.4 mm. thickness.
- ❖ **Hinge** is 19" Germany Export Rack products made from 3 pieces of high strength special PVC (ABS), rust-free and without any interfering noise. The reversibility of front and rear door opening from left of right by adjusting at one screw nut of hinge.
- ❖ **New Shine Light Gray** Two-Tone color by Electrostatic Powder Coating paint for scratch resistance.
- ❖ **Screw Set** compose of Screws, Captive nuts, Plastic washer; by each were coated with nickel and M6 thread system.
- ❖ **Manufacturing and Distribution** by ISO 9001:2008 Company.

Deliverly with

- 3 Master keys with trademark and number on the keys.
- 4 sets of wall mounting screw.
- Set of nut and screw according to the size of Rack.

Options

Color	Black or other
Thickness	1.6 mm or other

W=Width 600 mm. Standard

U	Overall H Height(mm.)	Order No. of Different Depth (mm.)			Figure
		D = 400	D = 500	D = 600	
1U=44.45mm.					
6U	320	G1-60406	G1-60506	G1-60606	A
9U	455	G1-60409	G1-60509	G1-60609	
12U	590	G1-60412	G1-60512	G1-60612	
6U	320	G1-60406P	G1-60506P	G1-60606P	B
9U	455	G1-60409P	G1-60509P	G1-60609P	
12U	590	G1-60412P	G1-60512P	G1-60612P	

* Order No. for Black Color : G1-XXXXXB

Sample : G1-60609B Wall Rack 9U, 60 x 60 cm., Black Color