

## ASCB6300LP

- Features :
- Terminal block for input
- Protections: Short circuit / Overload / Over voltage
- LED Indicator for power and charge
- Built-in Charger for Batteries.
- Zero Voltage Drop Upon Transfer to Battery Backup
- Automatic Switch Over to Stand-by Battery When AC Fails.



### SPECIFICATION

MODEL	ASCB6300LP	
OUTPUT	DC VOLTAGE	13.8V
	RATED CURRENT	4.34A
	CURRENT RANGE	0 ~ 5A
	RATED POWER	60W
	RIPPLE & NOISE (max.) <small>Note.2</small>	80mVp-p
	VOLTAGE ADJ. RANGE	12V~13.8V
INPUT	VOLTAGE RANGE	100 ~ 240VAC
	FREQUENCY RANGE	47 ~ 63Hz
PROTECTION	OVERLOAD	130% rated output power Protection type : Hiccup mode, recovers
	OVER VOLTAGE	15V
ENVIRONMENT	WORKING TEMP.	-0 ~ +40 °C (Refer to "Derating Curve")
	WORKING HUMIDITY	20 ~ 90% RH non-condensing
OTHERS	DIMENSION	220(L) mm*190(W) mm*70(H) mm
	PACKING	2.0Kg

