



## Magnetic Lock

| Product Name                            | Model     | Product Picture   | Basic Parameter  |
|---|-----------|---|--|
| One-door Electro-magnetic Lock (280KG)  | ASL-3202A |    | Lock Size: 250×47×25mm<br>Metal Board Size: 180×38×11mm<br>Working Voltage: DC12V<br>Support Door : Wooden Door, Glass Door, Metal Door, Fire-escape Door<br>Support Bearer: ASL-320L, ASL-320U, ASL-320ZL<br>Material : Aluminum  |
| One-door Electro-magnetic Lock (350KG)  | ASL-3203A |    | Lock Size: 285×49×28mm<br>Metal Board Size: 185×45×11mm<br>Working Voltage: DC12V<br>Support Door : Wooden Door, Glass Door, Metal Door, Fire-escape Door<br>Support Bearer: ASL-320L, ASL-320U, ASL-320ZL<br>Material : Aluminum  |
| One-door Electro-magnetic Lock (350KG)  | ASL-3202B |  | Lock Size: 250×47×25mm<br>Metal Board Size: 180×38×11mm<br>Working Voltage: DC12V<br>Support Door : Wooden Door, Glass Door, Metal Door, Fire-escape Door<br>Support Bearer: ASL-320L, ASL-320U, ASL-320ZL<br>Material : Aluminum  |
| Electric Bolt                           | ASL-3301+ |  | Standard Electric Bolt (4-core cable), with door magnet function and delay function<br>Type: Fail Safe Latch<br>Board: 90×25×2mm Lock<br>Size: 205×35×40mm<br>Working Voltage: DC12V±10%<br>Support Door: Wooden Door, Glass Door, metal door, fire-escape door<br>Support Bearer: ASF-330L, ASF-330U, ASF-330ZL<br>Material : Aluminum, stainless steel |
| Electro-magnetic Lock Bracket (ZL Type) | ASL-320ZL |  | Support Door : Wooden Door open toward inside, Metal Door, Narrow Frame Door<br>Door Open Mode : 90 degree one-way<br>Weight : 0.718kg<br>Material : Aluminum  |
| Electronic Lock Bracket                 | ASL-320L  |  | Support Door: Narrow Frame Door open toward inside<br>Door Open Mode: 90degree one-way or 180 degree two-ways<br>Glass Thickness: 8-15mm<br>Weight: 0.6kg<br>Material : Aluminum   |

## Magnetic Lock

| Product Name                                  | Model     | Product Picture   | Basic Parameter   |
|---|-----------|---|---|
| Electronic Lock Bearer (Glass Door)           | ASL-320U  |    | Support Door: Bottom Frameless Glass Door<br>Door Open Mode: 90 degree one-way or 180 degree two-way<br>Glass Thickness: 8-15mm<br>Weight: 0.3kg<br>Material : Aluminum   |
| Electric Bolt                                 | ASL-3302  |    | Electric Bolt(With Key)<br>Type: Fail Secure<br>Lock Size: 260x30x48mm<br>Latch Board: 100x25x2.7mm<br>Working Voltage: DC12V±10%<br>Support Door: Wooden Door, Glass Door, Metal Door, Fire-escape Door<br>Solid Bolt: polishing housing, 2000Kg Holding Force<br>Material : Aluminum, stainless steel |
| Electronic Lock Bearer (Glass Door)           | ASL-330L  |    | Support Door: Narrow Frame Door open toward inside<br>Door Open Mode: 90degree one-way or 180 degree two-ways<br>Glass Thickness: 8-15mm<br>Weight: 0.6kg<br>Material : Aluminum  |
| Electronic Lock Bearer (Glass Door)           | ASL-330U  |  | Support Door: Bottom Frameless Glass Door<br>Door Open Mode: 90 degree one-way or 180 degree two-way<br>Glass Thickness: 8-15mm<br>Weight: 0.3kg<br>Material : Aluminum   |
| Electronic Lock Bearer (Frameless Glass Door) | ASL-330ZL |  | Support Door: Glass Door with Frame<br>Door Open Mode: 90 degree one-way or 180 degree two-way<br>Glass Thickness: 8-15mm<br>Size: 204×58×46mm<br>Weight: 1.7kg<br>Material : Aluminum  |