









Exit Switch

Product Name	Model	Product Picture	Basic Parameter
Exit Button	ASF-EN20		Electric Parameter: Max. Current 3A@36VDC Contact Output: COM / NO Suitable for: Hollow Frame and Embedded Electric Case Size: 86×50×20mm Standard Structure: Aluminum Panel, Steel Button
Exit Button	ASF-EN30		Electric Parameter: Max. Current 3A@36VDC Contact Output: COM / NO Suitable for: Hollow Frame and Embedded Electric Case Size: 86×86×20mm Standard Structure: Aluminum Panel, Steel Button
Exit Button	ASF-EN40		Electric Parameter: Max. Current 3A@36VDC Contact Output: COM / NO S uitable for: Hollow Frame and Embedded Electric Case Size: 86×28mm Standard Structure: Stainless steel Panel, Steel Button
Exit Button	ASF-EN50		Electric Parameter: Max. Current 3A@36VDC Contact Output: COM / NO Suitable for: Hollow Frame and Embedded Electric Case Size: 86×86mm Standard Structure: Stainless steel Panel, Steel Button
Emergency Exit Button	ASF-EN80		Electric Parameter: Max. Current 3A@36VDC Contact Output: COM / NO / NC Suitable for: Break Glass in case of Emergency Color: Green/Red Standard Structure: Fireproof Material, Easy to install
Remote Entrance	ASF-EN90		Working Frequency: 2.4GHZ Size: 90×58×7mm Color: White Sensing Distance: 5-30m Material: ABS